



CONCRETE SIDEWALK

NOTE:

- 1) BANK SAND IS DEFINED AS A WELL-GRADED SAND, FREE OF SILT, CLAY, LOAM, FRIABLE OR SOLUBLE MATERIALS AND ORGANIC MATTER, MEETING THE UNIFIED SOILS CLASSIFICATION SYSTEM GROUP SYMBOL SW CRITERIA W/ A PLASTICITY INDEX OF  $\leq 10$ . AND NO MORE THAN 12% OF MATERIAL CAN PASS THE No. 200 SIEVE.
- 2) DOWEL IN AND TIE TO ANY CONCRETE STRUCTURE ADJACENT TO SIDEWALK (DRIVEWAY, INLET BOX, CURB, JUNCTION BOX, ETC.) WITH #3x12" BARS @ 18" O.C. INCLUDE EXPANSION JOINT AT CONNECTION WITH BACK OF CURB.

NOT TO SCALE

**CITY OF TOMBALL**  
ENGINEERING & PLANNING DEPARTMENT

**CONCRETE  
SIDEWALK  
CONSTRUCTION DETAILS**

APPROVED BY COT:

ENGINEERING & PLANNING DEPARTMENT  
EFFECTIVE NOVEMBER 19, 2018